



# **AC1200 Dual-band Router**

## **User Guide**

## Copyright Statement

© 2019 Shenzhen Tenda Technology Co., Ltd. All rights reserved.

**Tenda** is a registered trademark legally held by Shenzhen Tenda Technology Co., Ltd. Other brand and product names mentioned herein are trademarks or registered trademarks of their respective holders. Copyright of the whole product as integration, including its accessories and software, belongs to Shenzhen Tenda Technology Co., Ltd. No part of this publication can be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language in any form or by any means without the prior written permission of Shenzhen Tenda Technology Co., Ltd.

## Disclaimer

Pictures, images and product specifications herein are for references only. To improve internal design, operational function, and/or reliability, Tenda reserves the right to make changes to the products without obligation to notify any person or organization of such revisions or changes. Tenda does not assume any liability that may occur due to the use or application of the product described herein. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information and recommendations in this document do not constitute the warranty of any kind, express or implied.

## Preface

Thank you for choosing Tenda! Please read this user guide before you start.

## Conventions



This user guide is applicable to the following routers. AC8 is used for illustration in this guide unless it is specified. The contained images and UI screenshots are subject to the actual products.

Product model	Description
AC8	AC1200 Dual-band Gigabit Wireless Router
AC7	AC1200 Smart Dual-Band WiFi Router
AC5	AC1200 Smart Dual-band WiFi Router

Typographical conventions in this User Guide:

Item	Presentation	Example
Cascading Menus	>	Click <b>Status</b> > <b>Device Status</b>
Parameter and value	Bold	Set <b>User Name</b> to <b>Tom</b> .
UI control	Bold	On the <b>Policy</b> page, click the <b>OK</b> button.
Variable	Italic	Format: <i>XX:XX:XX:XX:XX:XX</i>
Message	“ ”	The “Success” message appears.

Symbols in this User Guide:

Item	Meaning
	This format is used to highlight information of importance or special interest. Ignoring this type of note may result in ineffective configurations, loss of data or damage to device.
	This format is used to highlight a procedure that will save time or resources.

## Acronyms and Abbreviations

Acronym or Abbreviation	Full Spelling
DDNS	Dynamic Domain Name System
DHCP	Dynamic Host Configuration Protocol
DMZ	Demilitarized Zone
DNS	Domain Name Server
IPTV	Internet Protocol Television

Acronym or Abbreviation	Full Spelling
IPv4	Internet Protocol Version 4
IPv6	Internet Protocol Version 6
ISP	Internet Service Provider
PPP	Point To Point Protocol
PPPoE	Point-to-Point Protocol over Ethernet
PPTP	Point to Point Tunneling Protocol
SSID	Service Set Identifier

## Technical Support

If you need more help, contact us by any of the following means. We will be glad to assist you as soon as possible.



**Hotline**

Global: (86) 755-27657180  
(China Time Zone)

United States: 1-800-570-5892  
(Toll Free: 7 x 24)

Canada: 1-888-998-8966  
(Toll Free: Mon - Fri 9 am - 6 pm PST)

Hong Kong: 00852-81931998



**Email**

support@tenda.cn

# Content

1	At a glance .....	4
1.1	Apperance .....	4
1.1.1	LED indicator .....	4
1.1.2	Ports and buttons.....	5
1.1.3	Label .....	5
2	Quick setup .....	7
3	Web UI.....	9
3.1	Logging in to the web UI .....	9
3.2	Logging out of the web UI.....	10
3.3	Web UI layout.....	11
4	Status.....	12
4.1	Internet connection status .....	12
4.2	Online devices and real-time speed.....	13
4.3	System information .....	14
5	Internet settings .....	15
5.1	Router mode .....	15
5.1.1	Setting up an internet connection with PPPoE .....	16
5.1.2	Setting up an internet connection with dynamic IP .....	17
5.1.3	Setting up an internet connection with static IP.....	18
5.2	WISP mode.....	19
5.3	Universal repeater mode .....	25
5.4	AP mode .....	30
6	Wireless settings .....	33
6.1	WiFi name and password .....	33
6.1.1	Overview .....	33
6.1.2	Customizing your WiFi name and password .....	34
6.2	Guest network.....	36
6.2.1	Overview .....	36
6.2.2	Setting up the guest network.....	37
6.3	WiFi signal strength.....	38
6.4	Wireless parameters .....	39


6.5	Beamforming+ .....	40
6.6	WPS .....	42
6.6.1	Overview .....	42
6.6.2	Connecting devices to the WiFi network using WPS .....	42
7	Bandwidth control.....	44
7.1	Configuring bandwidth control .....	45
7.2	Blocking a device .....	45
8	Parental controls .....	46
8.1	Overview .....	46
8.2	Setting up a parental controls rule.....	47
8.3	An example of configuring parental controls.....	48
9	Sleeping mode.....	49
9.1	Overview .....	49
9.2	LED control .....	50
9.3	WiFi schedule .....	51
9.3.1	Overview .....	51
9.3.2	An example of configuring WiFi schedule.....	51
10	Advanced.....	53
10.1	MAC address filter.....	53
10.1.1	Overview .....	53
10.1.2	Setting MAC address filter rules.....	53
10.1.3	An example of setting a MAC address filter rule .....	54
10.2	IPTV .....	56
10.2.1	Overview .....	56
10.2.2	An example of configuring IPTV .....	56
10.3	IP-MAC binding .....	58
10.3.1	Configuring an IP-MAC binding rule.....	58
10.4	Port forwarding .....	60
10.5	DDNS .....	62
10.5.1	Overview .....	62
10.5.2	An example of configuring DDNS.....	63
10.6	DMZ host.....	65
10.7	UPnP.....	66
10.8	Firewall.....	66
11	IPv6.....	67

11.1 Overview .....	67
11.2 Setting up an internet connection with DHCPv6 .....	70
11.3 Setting up an internet connection with PPPoEv6 .....	71
11.4 Setting up an internet connection with static IPv6 address .....	72
12 Administration.....	74
12.1 Login password.....	74
12.2 WAN parameters.....	75
12.3 LAN parameters.....	77
12.4 Remote web-based management.....	78
12.5 Date & Time .....	81
12.6 Device management .....	82
Appendix .....	87
A.1 Configuring the computer to obtain an IP address automatically.....	87
A.1.1 Windows 8 .....	87
A.1.2 Windows 7 .....	89
A.1.3 Windows 10 .....	91
A.2 Default parameters .....	93

# 1 At a glance

## 1.1 Appearance


### 1.1.1 LED indicator



LED indicator	Status	Description
	Solid on	The router is starting or connected to the internet successfully.
	Slow blinking	The router fails to connect to the internet.
	Fast blinking for 3 seconds	A wired device is connected or disconnected to the router.
LED indicator	Fast blinking for 8 seconds	The migration of PPPoE user name and password succeeds after you connect the WAN port of the original router to one of the LAN ports of the new router.
	Fast blinking for 2 minutes	The router is performing WPS negotiation.




## 1.1.2 Ports and buttons



Button/Port	Description
WPS/RST	<p>WiFi on/off button and reset button.</p> <ul style="list-style-type: none"> <li>• Hold the button down for 1~3 seconds to turn on or off the WiFi network of the router.</li> <li>• Hold the button down for about 8 seconds, and release it when the LED indicator blinks fast. The router is reset successfully.</li> </ul>
LAN1/2/3	Used to connect to wired devices such as computers or switches.
WAN	Used to connect this router to the internet.
PWR	Used to connect to the included power adapter.

## 1.1.3 Label

The bottom label shows the SSID, login IP address, serial number and MAC address of the router. See the following figure:



**IP Address:** It is the default address used to log in to the web UI of the router.

**MAC:** It specifies the MAC address of the router.

**S/N:** It is required if you need technical assistance to repair your device.

**SSID:** It specifies the default WiFi name of the router.

**Pin No.:** It specifies the PIN code of the router.

# 2 Quick setup

This chapter introduces how to quickly set up the router for the first time to access the internet.

**Step 1** Connect your router.


1. Power on the router using the power adapter included in the package.
2. Use an Ethernet cable to connect an Ethernet jack or a LAN port of your modem to the WAN port of the router.
3. Either connect your computer to a LAN port of the router, or connect your WiFi-enabled device, such as a smartphone, to the default WiFi name (SSID) of the router.



The default SSID is on the bottom [label](#) of the router.

**Step 2** Set up the router. (Here we use a computer to set up the router)

1. Start a web browser on the computer that has connected to the router, and visit **tendawifi.com** or **192.168.0.1**.



2. The router detects your connection type automatically. Set the parameters based on the detection result. PPPoE is used for instructions.
  - **User Name:** Enter the user name provided by your ISP.
  - **Password:** Enter the password provided by your ISP.
3. Customize the **WiFi Name** and **WiFi Password**, and click **OK**.



You can access the internet after completing settings on this page.

As detected, your connection type is: **PPPoE**



Internet

Connection Type  PPPoE  Dynamic IP Address  Static IP Address

This type is applicable if you have a user name and password for setting up a broadband dial-up connection. You can [import them from your original router](#).

User Name

Password



Wireless


WiFi Name

WiFi Password

OK

---End

The following figure displays, and you will be redirected to the home page in 3 seconds.




To access the internet, connect wireless devices to the WiFi network of the router again using the WiFi name and password you set, and connect your wired devices to port LAN1/2/3.

# 3 Web UI

## 3.1 Logging in to the web UI

**Step 1** Connect your smartphone to the wireless network, or connect your computer to ports LAN1/2/3 of the router.




**Step 2** Start a web browser on the device connected to the router, visit **tendawifi.com** or 192.168.0.1.



---End

The following page appears.




If the above page doesn't appear, check whether the computer is obtaining an IP address automatically. Refer to [A.1 configuring the computer to obtain an IP address automatically](#).

## 3.2 Logging out of the web UI

If you log in to the web UI of the router and perform no operation within 5 minutes, the router logs you out automatically. You can also log out by clicking **Logout** on the upper right corner of the web UI.

### 3.3 Web UI layout

The web UI of the router consists of two sections, including the navigation bar and the configuration area. See the following figure.




SN	Name	Description
1	Navigation bar	Used to display the function menu of the router. Users can select functions in the navigation bar and the configuration appears in the configuration area.
2	Configuration area	Used to modify or view your configurations.


# 4 Status


Log in to the web UI of the router and choose **Status** to enter the page. On this page, you can view the internet connection status of the router, online devices information and system information of the router.

## 4.1 Internet connection status

- If the message “Connected. You can access the internet” shows on the page, the internet is accessible.



- If a red cross  appears, the internet connection is abnormal. Please follow the onscreen instruction to resolve the issue.





## 4.2 Online devices and real-time speed

This section displays the number of online devices and the real-time upload/download speed.

Online Devices and Real-Time Speed

**1**  
Online Devices

**0.0** KB/s  
Download Speed

**0.0** KB/s  
Upload Speed

To control the bandwidth of online devices, click [Online Devices](#) to enter the configuration page.

- Status
- Internet Settings
- Wireless Settings
- Bandwidth Control**
- Parental Controls
- Sleeping Mode

Online Devices(1)

Device Name	Download Speed	Upload Speed	Download Limit	Upload Limit	Internet Access
MININT-K1N... 192.168.0.100	↓ 0KB/s	↑ 0KB/s	No limit	No limit	Local

Blacklisted Devices

Device Name	MAC Address	Unlimit
No device		

## 4.3 System information

This section displays the basic information of the router, including connection type, connection duration, WAN IP and so on.

System Information			
Connection Type	Dynamic IP Address	WAN IP Address	192.168.20.149
Connection Duration	2h 32m 59s	Subnet Mask	255.255.255.0
WAN MAC Address	C8:3A:35:17:F0:40	Default Gateway	192.168.20.100
LAN IP Address	192.168.0.1	Preferred DNS Server	192.168.20.100
Firmware Version	V02.03.01.50_multi	Alternate DNS Server	0.0.0.0

### Parameter description

Parameter	Description
Connection Type	It displays the current connection type of the router.
Connection Duration	It specifies the time that has elapsed since the router connects to the internet successfully.
WAN MAC Address	It specifies the MAC address of the WAN port of the router.
LAN IP Address	It specifies the IP address of the LAN port for the router.
Firmware Version	It specifies the current version number of the router's firmware.
WAN IP Address	It specifies the IP address of the WAN port.
Subnet Mask	It specifies the subnet mask of the WAN port.
Default Gateway	It specifies the default gateway of the WAN port.
Preferred DNS Server	It displays the preferred DNS server address of the WAN port.
Alternate DNS Server	It displays the Alternate DNS server address of the WAN port. If you do not set this parameter, it shows <b>0.0.0.0</b> .

# 5 Internet settings

On this page, you can complete the internet settings if you did not finish them by the quick setup wizard, or change the settings as well. The router supports Router, WISP, Universal Repeater and AP mode. By default, the router works in router mode.

## 5.1 Router mode

In router mode, this router can connect to the internet through the WAN port, and provide both wired and wireless network for clients. Applicable scenarios are as follows:



The following table may help you understand your internet connection type. If you are still uncertain about your internet connection type, consult your ISP.

Parameter	Description
PPPoE	If you directly connect an Ethernet cable with internet connectivity to your computer, you can access the internet only after setting up a dial-up connection

Parameter	Description
	on the computer using a user name and password provided by your ISP.
Dynamic IP	If you directly connect an Ethernet cable with internet connectivity to your computer, you can access the internet without configuring your computer.
Static IP Address	If you can access the internet only after setting static IP address and other related information on your computer, your connection type is static IP address.

### 5.1.1 Setting up an internet connection with PPPoE

**Step 1** Choose **Internet Settings** to access the configuration page.

**Step 2** Set **Operating Mode** to **Router**.

**Step 3** Set **Connection Type** to **PPPoE**.

**Step 4** Enter **User Name** and **Password** provided by your ISP.

**Step 5** Click **OK** at the bottom of the page.

Operating Mode

Router
  WISP
  Universal Repeater
  AP

In this mode, the router connects to an ISP in a wired manner and meanwhile provides WiFi signals, enabling clients to wirelessly access the internet.

Internet Connection

Connection Type
  PPPoE
  Dynamic IP Address
  Static IP Address

This type is applicable if you have a user name and password for setting up a broadband dial-up connection.

User Name

Password

**---End**

After the settings take effect, check the connection status. If **“Connected. You can access the internet.”** is displayed, the router is connected to the internet successfully.

Operating Mode

Router
  WISP
  Universal Repeater
  AP

In this mode, the router connects to an ISP in a wired manner and meanwhile provides WiFi signals, enabling clients to wirelessly access the internet.

---

Internet Connection

Connection Type
  PPPoE
  Dynamic IP Address
  Static IP Address

This type is applicable if you have a user name and password for setting up a broadband dial-up connection.

User Name

Password

Connection Status Connected. You can access the internet.

## 5.1.2 Setting up an internet connection with dynamic IP

- Step 1** Choose **Internet Settings** to access the configuration page.
- Step 2** Set **Operating Mode** to **Router**.
- Step 3** Set **Connection Type** to **Dynamic IP Address**.
- Step 4** Click **OK** at the bottom of the page.

Operating Mode

Router
  WISP
  Universal Repeater
  AP

In this mode, the router connects to an ISP in a wired manner and meanwhile provides WiFi signals, enabling clients to wirelessly access the internet.

---

Internet Connection

Connection Type
  PPPoE
  Dynamic IP Address
  Static IP Address

This type is applicable if no account or static IP address is required for setting up an internet connection.

---End

After the settings take effect, check the connection status. If “**Connected. You can access the internet.**” is displayed, the router is connected to the internet successfully.

Internet Connection

Connection Type
  PPPoE
  Dynamic IP Address
  Static IP Address

This type is applicable if no account or static IP address is required for setting up an internet connection.

Connection Status Connected. You can access the internet.

### 5.1.3 Setting up an internet connection with static IP

**Step 1** Choose **Internet Settings** to access the configuration page.

**Step 2** Set **Operating Mode** to **Router**.

**Step 3** Set **Connection Type** to **Static IP Address**.

**Step 4** Set the required parameters provided by your ISP.

**Step 5** Click **OK** at the bottom of the page.

The screenshot shows the 'Internet Connection' configuration page. At the top, there are three radio buttons for 'Connection Type': 'PPPoE', 'Dynamic IP Address', and 'Static IP Address'. The 'Static IP Address' option is selected. Below this, a note states: 'This type is applicable if a static IP address is required for setting up an internet connection.' The form contains five rows of input fields, each with four boxes separated by dots: 'IP Address', 'Subnet Mask', 'Default Gateway', 'Preferred DNS', and 'Alternate DNS'. The 'Alternate DNS' field has '(Optional)' written next to it.

---End


After the settings take effect, check the connection status. If **“Connected. You can access the internet.”** is displayed, the router is connected to the internet successfully.

This screenshot shows the same 'Internet Connection' configuration page as above, but now with numerical values entered in the input fields. The 'Connection Status' at the bottom is displayed in green text as 'Connected. You can access the internet.' The values are: IP Address (192, 168, 20, 155), Subnet Mask (255, 255, 255, 0), Default Gateway (192, 168, 20, 100), Preferred DNS (192, 168, 20, 100), and Alternate DNS (empty boxes).

## 5.2 WISP mode

In WISP mode, this router can connect to a WiFi hotspot provided by ISP in a wireless manner, and provide both wireless and wired network for clients to access internet.

Choose **Internet Settings** to access the configuration page.



Operating Mode


Router  WISP  Universal Repeater  AP

In this mode, the router connects to an ISP in a wired manner and meanwhile provides WiFi signals, enabling clients to wirelessly access the internet.

### Configuration procedure:

**Step 1** Log in to the web UI of the router.

**Step 2** (Optional). Set **Connection Type** to **Dynamic IP Address**, and click **OK**.



**Tenda**

You can access the internet after completing settings on this page.

As detected, your connection type is: **Dynamic IP Address**

**Internet**

Connection Type  PPPoE  Dynamic IP Address  Static IP Address

This type is applicable if you can access the internet without configuration after connecting the cable with internet connectivity to your computer.

**Wireless**

WiFi Name

WiFi Password

**OK**



This step applies to the first setup of the router. It is used for you to skip the quick setup page.

**Step 3** Choose **Internet Settings** to access the configuration page.

**Step 4** Set **Operating Mode** to **WISP**.

**Step 5** Select the **Connection Type** of your WiFi hotspot and enter the related parameters as required.

**Step 6** Select the WiFi name to connect.

Operating Mode

Router
  WISP
  Universal Repeater
  AP

In this mode, the router extends the WiFi signals of ISPs like CMCC, China Unicom, and ChinaNet.

---

Internet Connection

Connection Type       PPPoE    Dynamic IP Address    Static IP Address

This type is applicable if no account or static IP address is required for setting up an internet connection.

---

Select WiFi Network

Select	WiFi Name	MAC Address	Channel	Security Mode	Strength
<input type="radio"/>	000-cyl-ac9	d8:32:14:4c:cb:71	1	WPAWPA2/AES	📶 96%
<input checked="" type="radio"/>	Tenda_F011A0_EXT	c8:3a:35:db:40:e4	2	WPAWPA2/AES	📶 92%
<input type="radio"/>	AAAAAaaa	c8:3a:35:f5:86:71	4	None	📶 90%

**Step 7** If the wireless network of the upstream device is encrypted, enter the password of the upstream WiFi network.

**Enter Password** ✕

Enter the password of "Tenda\_F011A0\_EXT".

Password of the upstream WiFi network

Connect

When you click Connect, the router reboots to make the settings effective.  
Use [tendawifi.com](http://tendawifi.com) to log in to the web UI.

**Step 8** Click **Connect** and wait for the router to reboot.

**Reboot**

Rebooting... 3%

---End



Wait until the progress bar is complete. Log in to the web UI of the router again. Choose **Status > Internet Connection Status** to check the connection status.

## An example of configuring WISP mode

### Application scenario

Tom lives in the countryside, and it is not convenient for him to connect the nearest ISP base station using Ethernet cables. To solve the problem, he uses an AC8 router to extend wireless signal in his apartment, and sets the router to WISP mode to meet the requirement.

Tom's ISP provides a hotspot for internet with the information below:

- SSID: ISP\_A
- WiFi password: 87654321
- PPPoE user name: Tom
- PPPoE password: Tom123

### Network topology



### Configuration procedure:


**Step 1** Log in to the web UI of the router.

**Step 2** (Optional). Set **Connection Type** to **Dynamic IP Address**, and click **OK**.

You can access the internet after completing settings on this page.

As detected, your connection type is: **Dynamic IP Address**


---

 **Internet**

Connection Type  PPPoE  Dynamic IP Address  Static IP Address

This type is applicable if you can access the internet without configuration after connecting the cable with internet connectivity to your computer.

---

 **Wireless**

WiFi Name

WiFi Password



This step applies to the first setup of the router, they are used for you to skip the quick setup page.

- Step 3** Choose **Internet Settings** to access the configuration page.
- Step 4** Set **Operating Mode** to **WISP**.
- Step 5** Select the **Connection Type** of your ISP hotspot, which is **PPPoE** in this example. Enter the PPPoE user name and password provided by your ISP, which is **Tom/Tom123** in this example.

**Step 6** Choose the ISP hotspot, which is **ISP\_A** in this example.

Operating Mode

Router  WISP  Universal Repeater  AP

In this mode, the router extends the WiFi signals of ISPs like CMCC, China Unicom, and ChinaNet.

Internet Connection

Connection Type  PPPoE  Dynamic IP Address  Static IP Address

This type is applicable if you have a user name and password for setting up a broadband dial-up connection.

User Name

Password

Select WiFi Network

Select	WiFi Name	MAC Address	Channel	Security Mode	Strength
<input type="radio"/>	1.2-2.4	d8:38:0d:7f:80:12	8	None	📶 90%
<input type="radio"/>	1-2.4	d8:38:0d:7f:80:11	8	None	📶 90%
<input checked="" type="radio"/>	ISP_A	c8:3a:35:db:40:e4	11	WPAWPA2/AES	📶 88%


**Step 7** Enter the password of the WiFi network **ISP\_A**, which is **87654321** in this example.

Enter Password ✕

Enter the password of "ISP\_A".


When you click Connect, the router reboots to make the settings effective.  
Use [tendawifi.com](http://tendawifi.com) to log in to the web UI.

**Step 8** Click **Connect**.



**---End**

Wait until the progress bar is complete. Log in to the web UI of the router again with the domain name **tendawifi.com**. Choose **Status > Internet Connection Status** to check the connection status.



You can check the SSIDs for this router and the upstream device. If you need to change the router's SSID and password, please go to the [Wireless Settings](#) page.

## 5.3 Universal repeater mode

In universal repeater mode, the router can bridge the upstream wireless signals and expand your wireless network coverage.

Choose **Internet Settings** to access the configuration page.

Operating Mode

Router  WISP  Universal Repeater  AP

In this mode, the router connects to an ISP in a wired manner and meanwhile provides WiFi signals, enabling clients to wirelessly access the internet.

### Configuration procedure

**Step 1** Log in to the web UI of the router.


**Step 2** (Optional). Set **Connection Type** to **Dynamic IP Address**, and click **OK**.

**Tenda**

You can access the internet after completing settings on this page.

As detected, your connection type is: **Dynamic IP Address**


---

 **Internet**

Connection Type  PPPoE  **Dynamic IP Address**  Static IP Address

This type is applicable if you can access the internet without configuration after connecting the cable with internet connectivity to your computer.

---

 **Wireless**

WiFi Name

WiFi Password

**OK**



This step applies to the first setup of the router. It is used for you to skip the quick setup page.

**Step 3** Choose **Internet Settings** to access the configuration page.


**Step 4** Set **Operating Mode** to **Universal Repeater**.

**Step 5** Select the WiFi name to be extended.

Operating Mode

Router
  WISP
  Universal Repeater
  AP

In this mode, the router can extend any WiFi signals.

Select WiFi Network 

Select	WiFi Name	MAC Address	Channel	Security Mode	Strength
<input type="radio"/>	0124	50:2B:73:F0:3A:0B	11	None	97%
<input type="radio"/>	Tom's WiFi	D8:CE:3A:8F:71:24	13	WPA2/AES	97%
<input type="radio"/>	000-CYL	D8:32:14:4C:CB:71	10	WPAWPA2/AES	100%

**Step 6** If the wireless network of the upstream device is encrypted, set the password of the upstream WiFi network.

Enter Password ✕

Enter the password of "000-CYL".

Password of the upstream WiFi network

When you click Connect, the router reboots to make the settings effective.  
Use [tendawifi.com](http://tendawifi.com) to log in to the web UI.

**Step 7** Click **Connect** and wait for the router to reboot.

Reboot

Rebooting... 3%

**---End**

Wait until the progress bar is complete. Log in to the web UI of the router again. Choose **Status > Internet Connection Status** to check the connection status.


## An example of configuring universal repeater mode

### Application scenario

Tom uses a wireless router (main router) for internet access in his apartment. The router is placed in the main bedroom, so the WiFi signal is strong in the main bedroom, but too poor in the dining room and balcony to access the internet. To solve the problem, Tom bought a Tenda AC8 router, and placed it in the living room.

The universal repeater mode of AC8 can meet the requirement.

### Network topology



### Assumption

- SSID of the main router: Tom's WiFi
- WiFi password of the main router: 12345678
- WiFi security mode of the main router: WPA/WPA2-PSK Mixed

### Configuration procedure


**Step 1** Log in to the web UI of the router.

**Step 2** (Optional). Set **Connection Type** to **Dynamic IP Address**, and click **OK**.

You can access the internet after completing settings on this page.

As detected, your connection type is: **Dynamic IP Address**


---

 **Internet**

Connection Type  PPPoE  Dynamic IP Address  Static IP Address

This type is applicable if you can access the internet without configuration after connecting the cable with internet connectivity to your computer.

---

 **Wireless**

WiFi Name

WiFi Password




This step applies to the first setup of the router. It is used for you to skip the quick setup page.


- Step 3** Choose **Internet Settings** to access configuration the page.
- Step 4** Set **Operating Mode** to **Universal Repeater**.
- Step 5** Select the WiFi name to be extended, which is **Tom's WiFi** in this example.

Operating Mode

Router  WISP  Universal Repeater  AP


In this mode, the router can extend any WiFi signals.

Select WiFi Network 


Select	WiFi Name	MAC Address	Channel	Security Mode	Strength
<input checked="" type="radio"/>	Tom's WiFi	00:90:4c:88:88:89	7	WPAWPA2/AES	 94%

- Step 6** Enter the password of the selected WiFi network, which is **12345678** in this example.






**Step 7** Click **Connect**.



**---End**

Wait until the progress bar is complete. Log in to the web UI of the router again with the domain name **tendawifi.com**. Choose **Status > Internet Connection Status** to check the connection status and the SSIDs for this router and the upstream device.



To change the router's SSID and password, please go to the [Wireless Settings](#) page.

## 5.4 AP mode

In AP mode, the router connects to the internet using an Ethernet cable and converts wired network into wireless network to provide wireless network coverage. In AP mode, the WAN port also serves as a LAN port. Applicable scenarios are as follows:



Choose **Internet Settings** to access the configuration page.

Operating Mode

Router  WISP  Universal Repeater  AP

In this mode, the router connects to an ISP in a wired manner and meanwhile provides WiFi signals, enabling clients to wirelessly access the internet.

### Configuration procedure


**Step 1** Log in to the web UI of the router.

**Step 2** (Optional). Set **Connection Type** to **Dynamic IP Address**, and click **OK**.

You can access the internet after completing settings on this page.

As detected, your connection type is: **Dynamic IP Address**


---

 **Internet**

Connection Type  PPPoE  Dynamic IP Address  Static IP Address

This type is applicable if you can access the internet without configuration after connecting the cable with internet connectivity to your computer.

---

 **Wireless**

WiFi Name

WiFi Password



This step applies to the first setup of the router. It is used for you to skip the quick setup page.

**Step 3** Choose **Internet Settings** to access the configuration page.


**Step 4** Set **Operating Mode** to **AP**, and click **OK** at the bottom of the page.

Operating Mode

Router  WISP  Universal Repeater  AP

In this mode, the router functions as an AP, which is often used for wireless network coverage in hotels and SMEs.

**Step 5** Click **OK** in the popup window.



---End

When the router completes rebooting, the computer connected to the router by an Ethernet cable can access the internet, and wireless device such as smart phones can connect to the WiFi network of the router to access the internet.



- In AP mode, the router's network settings, VPN, parental controls, bandwidth control, virtual server and other functions will be not available.
  - In AP mode, the router's LAN IP address changes automatically to be in the same segment of the upstream device. You can log in to the web UI of the router with **tendawifi.com** instead of **192.168.0.1**.
-

# 6

# Wireless settings

## 6.1 WiFi name and password

### 6.1.1 Overview

This router supports 2.4 GHz and 5 GHz WiFi networks. Features of these two signals are listed as follows:

- 2.4 GHz signal has longer wireless transmission distance than 5 GHz signal.
- 2.4 GHz signal has better wall penetration capacity than 5 GHz signal.
- 5 GHz signal has higher wireless transmission speed than 2.4 GHz signal.
- 5 GHz is less congestion, interference, and more stable than 2.4 GHz signal.

You can set the WiFi names, encryption modes, and WiFi passwords for two WiFi networks on the **WiFi Name and Password** page. To access the configuration page, click **WiFi Settings** and move to **WiFi Name and Password** module.

#### WiFi Name and Password

Preferred Band  Enable  Disable

With this function enabled, the router has the same SSID both on 2.4 GHz and 5 GHz bands, and ensures that the WiFi devices are automatically connected to the WiFi network with stronger signals.

2.4 GHz Network  Enable  Disable

WiFi Name   Hide WiFi (?)

Security Mode

5 GHz Network  Enable  Disable

WiFi Name   Hide WiFi (?)

Security Mode

## Parameter description

Parameter	Description
Preferred Band	Used to turn on or off the Preferred Band function. When it is enabled, the WiFi names of 2.4 GHz and 5 GHz networks are the same. And only one WiFi signal is displayed. When you connect to the WiFi network, a better-quality WiFi signal will be automatically connected.
2.4 GHz Network/ 5 GHz network	Used to enable or disable the wireless networks of the router.
WiFi Name	It specifies the wireless network name (SSID) of the WiFi network.
Security Mode	It specifies the encryption modes supported by the router, including: <ul style="list-style-type: none"><li>• <b>None:</b> It indicates that a wireless network is not encrypted and any clients can access the network without a password. This option is not recommended as it leads to low network security.</li><li>• <b>WPA-PSK:</b> It indicates that WPA-PSK is adopted to authenticate users.</li><li>• <b>WPA2-PSK:</b> It indicates that WPA2-PSK is adopted to authenticate users.</li><li>• <b>WPA/WPA2-PSK Mixed:</b> It indicates that WPA-PSK and WPA2-PSK are adopted to authenticate users.</li></ul>
WiFi Password	Used to connect a wireless network. You are recommended to use the combination of digits, letters and special characters for higher security. Selecting <b>None</b> indicates that wireless clients can connect to the wireless network without entering a password. Select this option only when necessary since it leads to weak network security.
Hide WiFi	With this function enabled, wireless clients cannot detect the SSID, and you need to manually enter the SSID on the wireless clients to access the wireless network. By default, this function is disabled.

### 6.1.2 Customizing your WiFi name and password

**Step 1** Click **Wireless Settings** to enter the page, and locate to **WiFi Name and Password** module.

**Step 2** Customize your WiFi name, such as **Tenda WiFi**.

**Step 3** Set **Security Mode** to **WPA/WPA2-PSK Mixed** for better security and compatibility.

**Step 4** Specify your WiFi Password, such as **123456789**.

**Step 5** Click **OK** at the bottom of the page.

WiFi Name and Password

Preferred Band  Enable  Disable

With this function enabled, the router has the same SSID both on 2.4 GHz and 5 GHz bands, and ensures that the WiFi devices are automatically connected to the WiFi network with stronger signals.

WiFi Network  Enable  Disable

WiFi Name   Hide WiFi (?)

Security Mode

WiFi Password

**---End**

When the configurations complete, you need to re-connect to the new WiFi network with by entering the new password.

## 6.2 Guest network

### 6.2.1 Overview

In this module, you are able to enable/disable the Guest Network function and change guest network's WiFi name and password.

A guest network can be set up with a shared bandwidth limit for visitors to access the internet, and isolated from the main network. It protects the security and ensures the bandwidth of your main network.

To access the configuration page, click **Wireless Settings** and move to **Guest Network** module. By default, the Guest Network function is disabled. The following figure shows the interface when the function is enabled.

The screenshot shows the 'Guest Network' configuration interface. At the top, there is a title 'Guest Network'. Below it, there is a toggle switch for 'Guest Network' which is currently set to 'Enable'. Underneath, there are several input fields: '2.4 GHz WiFi Name' with the value 'Tenda\_VIP', '5 GHz WiFi Name' with the value 'Tenda\_VIP\_5G', and 'Guest Network Password' with the value 'Blank means no password'. There is also a 'Validity' dropdown menu set to '8 hours' and a 'Shared Bandwidth for Guests' dropdown menu set to 'Unlimited' with a unit of 'Mbps'.

#### Parameter description

Parameter	Description
Guest Network	Used to enable the Guest Network function. By default, this function is disabled.
2.4 GHz/ 5 GHz WiFi Name	It specifies the WiFi name of the router's guest network. By default, Tenda_VIP is for 2.4 GHz WiFi network and Tenda_VIP_5G for 5 GHz WiFi network. You can change the SSIDs if required. To distinguish the guest network from the main network, you are recommended not to set the same name for these four networks.
Guest Network Password	It specifies the password for the router's two guest networks. Please set the passwords according to your requirements.
Validity	It specifies the validity of the guest networks. The Guest Network function will be disabled automatically out of the specified time. Please set the validity as needed.
Shared Bandwidth for Guests	It allows you to specify the maximum download speed for all devices connected to the guest networks. By default, the bandwidth is not limited. You can set it as needed.



## 6.2.2 Setting up the guest network

**Step 1** Choose **Wireless Settings** to enter the page, and move to **Guest Network** module.

**Step 2** Set **Guest Network** to **Enable**.

**Step 3** Change **2.4 GHz WiFi Name**, such as to **Tom**.

**Step 4** Change **5 GHz WiFi Name**, such as to **Tom\_5G**.

**Step 5** Set **Guest Network Password**, such as to **987654321**.

**Step 6** Click the **Validity** drop-down box, and choose **4 hours**.

**Step 7** Click the **Shared Bandwidth for Guests** drop-down box, and choose **2**.

**Step 8** Click **OK** at the bottom of the page.

The screenshot shows the 'Guest Network' configuration interface. At the top, there is a title 'Guest Network'. Below it, the 'Guest Network' status is set to 'Enable' with a selected radio button, and 'Disable' is unselected. The '2.4 GHz WiFi Name' is set to 'Tom' in a text input field. The '5 GHz WiFi Name' is set to 'Tom\_5G' in a text input field. The 'Guest Network Password' is masked with '.....' in a text input field. The 'Validity' is set to '4 hours' in a dropdown menu. The 'Shared Bandwidth for Guests' is set to '2' in a dropdown menu, with 'Mbps' indicated to the right. The interface is clean and modern with a light gray background.

**---End**

After configuration, wireless devices such as smart phones, connected to **Tom** or **Tom\_5G** share a downloading speed of 2 Mbps, and can access the internet for 4 hours.


## 6.3 WiFi signal strength

In this module, you can adjust the wall-penetration capability and wireless coverage of the router. To access the configuration page, click **Wireless Settings** and move to **WiFi Signal Strength** module.

WiFi Signal Strength

2.4 GHz Signal Strength     High    Medium    Low

5 GHz Signal Strength     High    Low

Parameter	Description
2.4/ 5 GHz Signal Strength	<p>The mode of signal strength. The default mode is <b>High</b>.</p> <ul style="list-style-type: none"><li>• <b>High:</b> It is typically used to meet wireless coverage requirements in small area or barrier-free environments.</li><li>• <b>Medium:</b> It is typically used to meet wireless coverage requirements in medium-area or less-obstacle environments.</li><li>• <b>Low:</b> It is typically used to meet wireless coverage requirements in large or multi-barrier environments.</li></ul> <p> <b>TIP</b></p> <p>If the WiFi function works properly in low mode, you are recommended to select the low mode.</p>

## 6.4 Wireless parameters

In this section, you are allowed to change network mode, WiFi channel, and WiFi bandwidth of either 2.4 GHz or 5 GHz WiFi network.

To access the configuration page, click **Wireless Settings** and move to **Wireless Parameters** module.

Wireless Parameters

---

2.4 GHz Network

Network Mode

Wireless Channel  Current Channel:8

Wireless Bandwidth  Current bandwidth:20MHz

---

5 GHz Network

Network Mode

Wireless Channel  Current Channel:149

Wireless Bandwidth  Current bandwidth:80MHz

### Parameter description

Parameter	Description
Network Mode	<p>It specifies various protocols adopted for wireless transmission.</p> <ul style="list-style-type: none"><li>• <b>11b/g mixed</b>: It indicates that devices compliant with IEEE 802.11b or IEEE 802.11g protocol can connect to the router.</li><li>• <b>11b/g/n mixed</b>: It indicates that all devices working at 2.4 GHz and compliant with IEEE 802.11b, IEEE 802.11g, or IEEE 802.11n protocol can connect to the router.</li><li>• <b>11n</b>: It indicates that devices working at 2.4 GHz and compliant with IEEE 802.11n can connect to the router.</li><li>• <b>11ac</b>: It indicates that devices complaint with IEEE 802.11ac protocol can connect to the router.</li><li>• <b>11a/n/ac mixed</b>: It indicates that devices working at 5 GHz and compliant with IEEE 802.11a, IEEE 802.11n or IEEE 802.11ac protocol can connect to the router.</li></ul>
WiFi Channel	<p>It specifies the operating channel of a WiFi network.</p> <p>By default, the WiFi channel is <b>Auto</b>, which indicates that the router selects a channel for the wireless network automatically. But you can change it as required. You are recommended to choose a channel with less interference for better wireless transmission efficiency. You can use a third-party tool to scan the WiFi signals nearby to understand the channel usage situations.</p>

Parameter	Description
	<p>It specifies the bandwidth of the WiFi channel of a WiFi network. Change the default settings only when necessary.</p> <ul style="list-style-type: none"> <li>• <b>20</b>: It indicates that the channel bandwidth of a router is to 20 MHz.</li> <li>• <b>40</b>: It indicates that the channel bandwidth of a router is 40 MHz.</li> </ul>
WiFi Bandwidth	<ul style="list-style-type: none"> <li>• <b>20/40</b>: It specifies that a router can switch its channel bandwidth between 20 MHz and 40 MHz based on the ambient environment. This option is available only at 2.4 GHz.</li> <li>• <b>80</b>: It indicates that the channel bandwidth of a router is 80 MHz. This option is available only at 5 GHz.</li> <li>• <b>20/40/80</b>: It specifies that a router can switch its channel bandwidth among 20 MHz, 40 MHz, and 80 MHz based on the ambient environment. This option is available only at 5 GHz.</li> </ul>

## 6.5 Beamforming+

Beamforming is a radio wave technology written into the next generation IEEE Wi-Fi 802.11ac standard. Traditionally, the router broadcasts the data in all directions when broadcasting a Wi-Fi signal. With beamforming, the router transmits radio signal in the direction of the client, thus creating a stronger, faster and more reliable wireless communication.

The key benefits of beamforming are:

- Extended Wi-Fi coverage and fewer dead spots.
- Stable Wi-Fi connection for voice and HD video.
- Better Wi-Fi throughput.
- Less unnecessary RF interference.

The following figure shows the wireless transmission when Beamforming+ is disabled.



The following figure shows the wireless transmission when Beamforming+ is enabled.



To access the configuration page, click **Wireless Settings** and move to the **Beamforming+** module. By default, the Beamforming+ function is enabled.

Beamforming


Beamforming  Enable  Disable

## 6.6 WPS

### 6.6.1 Overview

The WPS function enables wireless devices such as smartphones to connect to WiFi networks of the router quickly and easily.

To access the configuration page, click **Wireless Settings** and move to the **WPS** module. It is enabled by default.




### 6.6.2 Connecting devices to the WiFi network using WPS



This function is only applicable to WPS-enabled wireless devices.

#### Method 1: Through the web UI of the router

- Step 1** Click **Wireless Settings** and move to the **WPS** module.
- Step 2** Click **PBC**.
- Step 3** Set WPS on a smart phone or computer installed with wireless network adapter within 2 minutes.



---End

Wait until the smart phone or computer is connected to the WiFi network of the router successfully.

#### Method 2: Through the WPS button on the router

- Step 1** Press the **WPS** button on the router. The LED indicator blinks fast.



**Step 2** Set WPS on a smart phone or computer installed with wireless adapter within two minutes.

---End

Wait until the smart phone or computer is connected to the WiFi network of the router successfully.

### Method 3: Through pin code of the router



WPS connection using pin code is generally applied on a computer with a wireless adapter. Please refer to relevant adapter's user guide for detailed instructions.

**Step 1** Click **Wireless Settings** and move to the **WPS** module.

**Step 2** Record the pin number of the router.

WPS

WPS  Enable  Disable

PBC Mode  Click this button or press the WPS/RESET button.

PIN Mode  Enter this PIN on the device to be connected.

**Step 3** Enter the pin code on the wireless device for connection.

---End


Wait until the smart phone or computer is connected to the WiFi network of the router successfully.

# 7




# Bandwidth control

In this section, you are allowed to view on-line device(s), block unknown device(s), and set maximum download/upload speed for online devices.

Click **Bandwidth Control** to enter the configuration page.



## Parameter description

Parameter	Description
Online Devices	<p>Device Name</p> <p>It displays the information of the online device, including device name, IP address and MAC address.</p> <p>You can click  to customize the device name for easier management.</p>
	<p>Download/Upload Speed</p> <p>It specifies the current upload and download speeds of the corresponding device.</p>
	<p>Upload/Download Limit</p> <p>It allows you to specify the maximum upload and download speeds for the corresponding device.</p>
	<p>Internet Access</p> <p>It allows you to allow/disallow the corresponding device to access the internet through the router. The current management computer cannot be controlled. <b>Local</b> stands for the device which is managing the router currently.</p> <p> : It indicates that the device is able to access the internet.</p> <p> : It indicates that the device is unable to access the internet.</p>
Blacklisted Devices	<p>Device Name</p> <p>It specifies the device name of a blocked device.</p>
	<p>MAC Address</p> <p>It specifies the MAC address of a blocked device.</p>



Parameter	Description
Unlimit	Used to remove a blocked device from the blacklist. After being removed from the blacklist, the device can reconnect to the router for internet access.

## 7.1 Configuring bandwidth control

**Step 1** Click **Bandwidth Control** to enter the configuration page.

**Step 2** Specify **Download/Upload Limit** as required.






**Step 3** Click **OK** at the bottom of the page.

---End

## 7.2 Blocking a device

**Step 1** Click **Bandwidth Control** to enter the configuration page.


**Step 2** Click  corresponded to the device to be blocked to change the status to .

Online Devices(2)					
Device Name	Download Speed	Upload Speed	Download Limit	Upload Limit	Internet Access
 MININT-K1N...  192.168.0.100 74:27:ea:69:80:04	↓ 0Kbps	↑ 0Kbps	No limit ▾	No limit ▾	Local
 MI8  192.168.0.101 d8:ce:3a:8f:71:24	↓ 0Kbps	↑ 0Kbps	No limit ▾	No limit ▾	

**Step 3** Click **OK** at the bottom of the page.

---End

The blocked device is displayed automatically in the blacklist. Click **Unlimit** to unblock a device from the blacklist.

Blacklisted Devices		
Device Name	MAC Address	Unlimit
MI8	D8:CE:3A:8F:71:24	


# 8

# Parental controls


## 8.1 Overview

The parental controls function allows you to block inappropriate and malicious websites, and control online devices to access allowed websites at allowed time.

Choose **Parental Controls** to enter the configuration page.



### Parameter description



Parameter	Description
Online Devices	Device Name It specifies the name of the online device. You can click  to customize the device name for easier management.
	IP Address It specifies the IP address of the online device.
	Online Duration It specifies the time that has elapsed since the device connects to the router successfully.
	Manage It specifies the status of a rule. You can enable/disable the rule by switching the button.
Access Restrictions	Allow access during It specifies the time period when internet connection is allowed.
	Repeat It specifies the dates The dates when internet connection is allowed.
	Website Restrictions It specifies the modes of website restrictions. <ul style="list-style-type: none"><li>• <b>Disable</b>: It specifies that all websites are accessible.</li><li>• <b>Only Permit</b>: It specifies that only the websites listed in <b>Unblocked Websites</b> are accessible.</li><li>• <b>Only Forbid</b>: It specifies that only the websites listed in <b>Blocked Websites</b> are inaccessible.</li></ul>


## 8.2 Setting up a parental controls rule

Configuration procedure:



A parental controls rule takes effect based on the IP address. Thus, to ensure that the rule takes effect correctly, you are recommended to use the IP-MAC binding function to bind an IP address to the device you want to control. Refer to [IP-MAC binding](#) for details.

- Step 1** Choose **Parental Controls** to enter the configuration page.
- Step 2** Set the button under **Manage** from  to  state.
- Step 3** Set the period at which the rule takes effect.
- Step 4** Set the date on which the rule takes effect.
- Step 5** Select a **Website Restrictions** mode, and set the websites allowed or disallowed.

Device Name	IP Address	Online Duration	Manage
MININT-K1N741G	192.168.0.100	3h 43m 3s	

Access Restrictions

Settings below will be applied to all managed devices

Allow access during: 19:00 ~ 21:00

Repeat:  Everyday  Mon.  Tue.  Wed.  Thu.  Fri.  Sat.  Sun.

Website Restrictions: Only Permit

Unblocked Websites: Enter website (+)

OK Cancel

- Step 6** Click **OK** at the bottom of the page.

---End



## 8.3 An example of configuring parental controls





Tom uses AC8 to set up a network in his apartment. He wants his daughter Cindy to focus on her homework from 20:00 to 22:00 instead of YouTube video on weekdays.

The parental controls function can meet this requirement.

**Configuration procedure:**

**Step 1** Choose **Parental Controls** to enter the configuration page.


**Step 2** Click the button  to change the state to  corresponding to **Sindy's phone**.



Online Devices				
Device Name		IP Address	Online Duration	Manage
MININT-K1N741G		192.168.1.100	1h 13m 19s	
Sindy's phone		192.168.1.101	2m 16s	

**Step 3** Set **Allow access during** to the period when the device is allowed to access video websites, which is **20:00-22:00** in this example.

**Step 4** Set the date on which the rule takes effect, which is Monday to Friday in this example.

**Step 5** Set **Website Restrictions** to **Only Forbid**.

**Step 6** Set **Blocked Websites** to **www.youtube.com**, and click .

Access Restrictions	
Settings below will be applied to all managed devices	
Allow access during	20 : 00 ~ 22 : 00
Repeat	<input type="checkbox"/> Everyday <input checked="" type="checkbox"/> Mon. <input checked="" type="checkbox"/> Tue. <input checked="" type="checkbox"/> Wed. <input checked="" type="checkbox"/> Thu. <input checked="" type="checkbox"/> Fri. <input type="checkbox"/> Sat. <input type="checkbox"/> Sun.
Website Restrictions	Only Forbid
Blocked Websites	Enter website 
1	www.youtube.com 

**Step 7** Click **OK** at the bottom of the page.

**---End**

After the settings take effect, Sindy's smart phone cannot access YouTube from 20:00 to 22:00 on weekdays.

# 9

# Sleeping mode


## 9.1 Overview

This router supports the Sleeping Mode function. With this function enabled, the router disables the LED indicator and WiFi network to reduce consumption during the specified time.



To make the Sleeping Mode function work properly, please ensure the system time is synchronized with the internet time.


To access the configuration page, click **Sleeping Mode**.



## 9.2 LED control

This page allows you to turn on and turn off the LED indicator of the router as required.

To access the configuration page, click **Sleeping Mode**, and move to the **LED Control** module.



### Parameter description

Parameter	Description
Always open	It indicates that the LED indicator works in ordinary states.
Always off	It indicates that the LED indicator is off even when the router is working.
Close Schedule	It specifies that the LED indicator is turned off as scheduled.

## 9.3 WiFi schedule

### 9.3.1 Overview

This WiFi Schedule function allows you to disable the WiFi network of the router at specified period. By default, this function is disabled.

To access the configuration page, click **Sleeping Mode**, and move to the **WiFi Schedule** module.


WiFi Schedule

WiFi Schedule  Enable  Disable

Turn WiFi Off At 00 : 00 ~ 07 : 00

Turn WiFi Off On  Everyday  Mon.  Tue.  Wed.  Thu.  Fri.  Sat.  Sun.

How to enable WiFi?



To enable/disable your WiFi anywhere and anytime, scan the QR code to download the Tenda WiFi app, register an account and bind it to the router.

or

Use an Ethernet cable to connect your router to your computer, enter [tendawifi.com](http://tendawifi.com) in the address bar of a web browser on the computer, and enable WiFi on the WiFi Settings page.

#### Parameter description

Parameter	Description
WiFi Schedule	Used to enable/disable the WiFi Schedule function.
Turn WiFi Off At	It specifies the period when the WiFi network is disabled. In that period, wireless devices cannot search the router's WiFi networks.
Turn WiFi Off On	It allows you to customize your WiFi schedule. See the following: <ul style="list-style-type: none"><li>• <b>Every Day:</b> The router disables its WiFi networks at the specified time you set every day.</li><li>• <b>Specified Day:</b> The router disables its WiFi networks at the specified time you set on specified days.</li></ul>

### 9.3.2 An example of configuring WiFi schedule

#### Scenario

Tom bought an AC8 for network coverage. To ensure a healthier sleeping environment, he wants to disable the WiFi networks every day during 23:00 to 7:00.

#### Procedures


**Step 1** Choose **Sleeping Mode**, and move to the **WiFi Schedule** module.

**Step 2** Set **WiFi Schedule** to **Enable**.

**Step 3 Turn WiFi Off At:** Set the period as needed, which is **23:00~07:00** in this example.

**Step 4 Turn WiFi Off On:** Select the schedule type as needed, which is **Every Day** in this example.

**Step 5** Click **OK** at the bottom of the page.



The screenshot shows a 'WiFi Schedule' configuration window. It contains three main sections: 1. A 'WiFi Schedule' section with radio buttons for 'Enable' (selected) and 'Disable'. 2. A 'Turn WiFi Off At' section with four dropdown menus showing the time '23:00~07:00'. 3. A 'Turn WiFi Off On' section with checkboxes for 'Everyday', 'Mon.', 'Tue.', 'Wed.', 'Thu.', 'Fri.', 'Sat.', and 'Sun.', all of which are checked.

**---End**

## Verification

The WiFi networks are disabled from 23:00 to 07:00 every day.



# 10

# Advanced

## 10.1 MAC address filter

### 10.1.1 Overview

This function allows you to set a MAC address whitelist or a blacklist to enable or disable users to access the internet through the router.

Choose **Advance** and move to the **MAC Address Filter** module to access the configuration page.

Blacklisted MAC Address	Remark (Optional)	Operation
<input type="text"/>	<input type="text"/>	+

#### Parameter description


Parameter	Description
Filter Mode	<ul style="list-style-type: none"><li>• <b>Blacklist:</b> Only the users with listed MAC addresses are not allowed to access the internet.</li><li>• <b>Whitelist:</b> Only the users with listed MAC addresses are allowed to access the internet.</li></ul>
Blacklisted/Whitelisted MAC Address	It specifies the MAC addresses to which a rule applies.
Remark (Optional)	It specifies the description of a rule.
Operation	<ul style="list-style-type: none"><li>⊕: Click it to add a device into the blacklist/whitelist.</li><li>⊖: Click it to delete a device from the blacklist/whitelist.</li></ul>

### 10.1.2 Setting MAC address filter rules

#### Adding a rule

- Step 1** Choose **Advanced** to enter the configuration page, and move to the **MAC Address Filter** module.
- Step 2** Select a **Filter Mode**.
- Step 3** Enter the MAC address to which the rule applies.
- Step 4** Enter remark information, which is optional.
- Step 5** Click ⊕.

**Step 6** Click **OK** at the bottom of the page.



Blacklisted MAC Address	Remark (Optional)	Operation
<input type="text"/>	<input type="text"/>	+


---End

### Deleting a rule

**Step 1** Click **Advanced** to enter the configuration page, and move to the **MAC Address Filter** module.

**Step 2** Click  $\ominus$  corresponded to the MAC address filtering rule to be deleted.

**Step 3** Click **OK** at the bottom of the page.



Blacklisted MAC Address	Remark (Optional)	Operation
<input type="text"/>	<input type="text"/>	+
8C:0D:76:E8:43:15		-

---End

## 10.1.3 An example of setting a MAC address filter rule

A family uses AC8 to access the internet. Recently an unknown device is found in the **Online Device** list. Under such circumstance, the MAC address filter function can be used to disallow the unknown device to connect to the WiFi network of the router for internet access.

Assume that the MAC addresses of the unknown device is D8:CE:3A:8F:71:24.

### Configuration procedure:

**Step 1** Choose **Advanced > MAC Address Filter**.

**Step 2** Set **Filter Mode** to **Blacklist**.

**Step 3** Enter the MAC address to be disallowed to access the internet, which is **D8:CE:3A:8F:71:24** in this example.

**Step 4** Enter the remark information of the device, which is **Unknown device** in this example.

**Step 5** Click  $\oplus$  .

**Step 6** Click **OK** at the bottom of the page.

MAC Address Filter

Filter Mode

- Blacklist (Disallow only listed MAC addresses.)
- Whitelist (Allow only listed MAC addresses.)

Blacklisted MAC Address	Remark (Optional)	Operation
<input type="text"/>	<input type="text"/>	<input type="button" value="⊕"/>
D8:CE:3A:8F:71:24	Unknown device	<input type="button" value="⊖"/>

**---End**

After you complete the settings, the unknown device cannot connect to the WiFi network to access the internet.


## 10.2 IPTV

### 10.2.1 Overview

IPTV is the abbreviation of Internet Protocol Television. It is new technology integrating with internet, multimedia, telecommunication and many other technologies, providing interactive services including digital TV to family users by internet broadband lines. IPTV is a service provided by ISP. Users can have multiple IPTV programs by IP set-top-box and television at home.

To access the configuration page, click **Advanced Settings** and move to the **IPTV** module.

The following figure appears after IPTV is enabled:



#### Parameter description


Parameter	Description
IPTV	Used to enable and disable the IPTV function of the router. When this function is enabled, the port <b>IPTV/3</b> can be used only as an IPTV port to be connected with an IPTV set-top-box.
VLAN	<p>It specifies the VLAN ID of your IPTV service.</p> <ul style="list-style-type: none"><li>• If you do not have any information about VLAN provided by your ISP when IPTV service is available, please keep <b>Default</b>.</li><li>• If you have VLAN ID from your ISP when IPTV service is available, please choose <b>Custom</b> VLAN and enter the VLAN value.</li><li>• If your IPTV service is Shanghai, please choose <b>Shanghai</b> VLAN and enter the VLAN value.</li></ul>

### 10.2.2 An example of configuring IPTV

#### Scenario

Tom subscribed to IPTV service from his ISP. His ISP provided IPTV account and password but no information about VLAN. After buying an AC8 to provide network, Tom wants to enjoy IPTV programs. The IPTV function of the router can address this requirement

## Network topology



## Procedure

**Step 1** Set you router.

1. To access the configuration page, click **Advanced Settings**, and move to **IPTV** module.
2. Set **IPTV** to **Enable**.
3. Click **OK** at the bottom of the page.

The screenshot shows the IPTV configuration page. At the top, it says "IPTV". Below that, there is a section for "IPTV" with two radio buttons: "Enable" (which is selected) and "Disable". Below the radio buttons, there is a text instruction: "Connect the IPTV STB to the IPTV port of the router." At the bottom, there is a "VLAN" section with a dropdown menu currently set to "Default".

**Step 2** Dial up on set-top-box with the account and password provided by ISP.

---End


## Verification

Tom can watch IPTV programs on television.

## 10.3 IP-MAC binding



The IP-MAC Binding function enables clients to obtain a fixed IP address, ensuring that the IP address-based functions, such as port forwarding, DMZ host and other functions of the router can take effect properly. This function is only effective when the DHCP server of the router is enabled.

Choose **Advanced**, and move to the **IP-MAC Binding** module to access the configuration page.




The screenshot shows the 'IP-MAC Binding' configuration page. It features a table with three columns: 'IP Address', 'MAC Address', and 'Operation'. The 'IP Address' and 'MAC Address' columns contain empty text input boxes. The 'Operation' column contains a plus sign icon (+) in a circle.


### Parameter description

Parameter	Description
IP Address	It specifies the IP address to be reserved for the client with the specified MAC address. It should belong to the DHCP address pool.
MAC Address	It specifies the MAC address of the client that needs a fixed IP address.
Operation	 : It is used to add an IP-MAC binding rule.  : It is used to delete an IP-MAC binding rule.

### 10.3.1 Configuring an IP-MAC binding rule

#### Adding a rule

- Step 1** Choose **Advanced** to enter the configuration page, and move to the **IP-MAC Binding** module.
- Step 2** Enter an IP address included in the DHCP address pool.
- Step 3** Enter the MAC address of the client which needs a fixed IP address.
- Step 4** Click .
- Step 5** Click **OK** at the bottom of the page.




The screenshot shows the 'IP-MAC Binding' configuration page after a rule has been added. The table now contains two rows. The first row has empty input boxes for 'IP Address' and 'MAC Address', and a plus sign icon (+) in the 'Operation' column. The second row contains the values '192.168.0.100' for 'IP Address', '74:27:EA:69:80:04' for 'MAC Address', and a minus sign icon (-) in the 'Operation' column.

---End

## Deleting a rule

**Step 1** Choose **Advanced** to enter the configuration page, and move to the **IP-MAC Binding** module.

**Step 2** Click  corresponded to an entry to be deleted.


**Step 3** Click **OK** at the bottom of the page.

**---End**

## 10.4 Port forwarding

By default, internet users cannot access any service on any of your local hosts. If you want to enable internet users to access a particular service on a local host, enable this function and specify the IP address and service port of the local host. This can also prevent local network from being attacked when the internal server is opened to the internet users.

Click **Advanced**, and move to the **Port Forwarding** module to access the configuration page.


Internal IP Address	Internal Port	External Port	Protocol	Operation
<input type="text"/>	21	21	Both	

### Parameter description

Parameter	Description
Internal IP Address	It specifies the IP address of a server that resides on the LAN.
Internal Port	It specifies the service port number of the internal server.
External Port	It specifies the service port number for internet users to access a specified service.
Protocol	It specifies the protocol that specified service uses. <b>Both</b> indicates that both TCP and UDP are used. If you are uncertain about it, <b>Both</b> is recommended.
Operation	It allows you to manually add and delete a port forwarding rule.

### An example of configuring a port forwarding rule

Tom uses an AC8 to set up home network, and establishes a web server in LAN. Now he wants internet users to access the resources on the server. The port forwarding function can be enabled to meet the requirement.





## Prerequisites

- The WAN IP address of the router is a public IP address, which is **102.33.66.88**.
- Computer 1 is assigned a fixed IP address, which is 192.168.0.100 (Refer to the [IP-MAC binding](#) function).
- The internal and external port of the web server is 89.

## Configuration procedure:

**Step 1** Choose **Advanced**, and move to **Port Forwarding** to enter the configuration page.

**Step 2** Enter **Internal IP** to the IP address of the web server, which is the IP address of computer 1, **192.168.0.100**.

**Step 3** Enter **Internal Port** to the port number of the web service, which is **89** in this example.

**Step 4** Enter **External Port**, which is **89** in this example.

**Step 5** Set **Protocol** to **Both**.


**Step 6** Click **+**, and then click **OK** at the bottom of the page.

Port Forwarding				
Internal IP Address	Internal Port	External Port	Protocol	Operation
<input type="text"/>	89	89	Both	<b>+</b>
192.168.0.100	89	89	Both	<b>-</b>

----End

## Verification

Enter *Protocol name://WAN port IP address:External port* in the address bar of a web browser on a computer over the internet to access the resources on the web server. In this example, enter **http://102.33.66.88:89**.



### NOTE

To make the port forwarding function always effective, you can use both the port forwarding function and DDNS functions to allow internet users to access the LAN server using a domain name.


## 10.5 DDNS

### 10.5.1 Overview

DDNS is short for Dynamic Domain Name Server. When the DDNS service runs, the DDNS client on the router sends its current WAN port IP address to the DDNS server, and then the server updates the mapping relationship between the domain name and the IP address in the database to achieve dynamic domain name resolution. You can enable this function to map the router's dynamically changing WAN Port IP address (public network IP address) to a fixed domain name.

DDNS normally interworks with port forwarding, DMZ host and remote web-based management, so that the internet users can access the internal server or the router's web UI with a domain name.

Choose **Advanced**, and move to the **DDNS** module to access the configuration page. By default, it is disabled. Select **Enable**, and the following page appears.



DDNS

DDNS  Enable  Disable

Service Provider  [Register Now](#)

DDNS User Name

DDNS Password

Connection Status

#### Parameter description

Parameter	Description
DDNS	It specifies whether to enable the DDNS function.
Service Provider	It specifies a DDNS service provider. The router supports oray.org and 88ip.cn.
DDNS User Name	It specifies the user name registered on a DDNS service provider's website for logging in to the DDNS service.
DDNS Password	It specifies the password registered on a DDNS service provider's website for logging in to the DDNS service.
Connection Status	It specifies the current connection status of the DDNS service.

## 10.5.2 An example of configuring DDNS

Winnie uses AC8 to set up network, and establishes a web server on LAN. She wants internet users to access the resources on the server with a domain name. The port forwarding function and DDNS function can be enabled to meet the requirement.

### Assumption

DDNS service provider: oray.com

Domain name: tenda-winnie.imwork.net


Username: tenda-winnie

Password: a1234578

Web server IP address: 192.168.0.110

Port number of the web server: 8080

### Network topology



Computer 1 (web server)

### Configuration procedure

**Step 1** Refer to [Port forwarding](#) to configure the port forwarding function.

Port Forwarding				
Internal IP Address	Internal Port	External Port	Protocol	Operation
<input type="text"/>	8080	8080	Both	+
192.168.0.110	8080	8080	Both	-

**Step 2** Configure the DDNS function.

1. Choose **Advanced**, and move to **DDNS** to enter the configuration page.

2. Set **DDNS** to **Enable**.
3. Set **Service Provider** to **oray.com**.



If you do not have a DDNS account, select a service provider and click [Register Now](#) to go to the service provider's website. Register a DDNS account and memorize your user name, password, and domain name of the account.

4. Enter your DDNS user name, which is **tenda-winnie** in this example.
5. Enter your DDNS password, which is **a12345678** in this example.

DDNS

DDNS  Enable  Disable

Service Provider  [Register Now](#)

DDNS User Name

DDNS Password

Connection Status

6. Click **OK** at the bottom of the page.

**---End**

Wait a moment, and refresh the page. When the **Connection Status** shows **Connected**, the configuration is saved successfully.

DDNS

DDNS  Enable  Disable

Service Provider  [Register Now](#)

DDNS User Name

DDNS Password

Connection Status **Connected**


## Verification

Internet users can use <http://tenda-winnie.imwork.net:8080> to access the web server.

## 10.6 DMZ host

A DMZ host on a LAN can be accessed by the internet users without limit. It is especially used for video conferences and online games. You can set a computer with these requirements as a DMZ host for better user experience.

Choose **Advanced**, and move to the **DMZ Host** module to access the configuration page. By default, it is enabled. It shows as the following figure when you enable it.




### NOTE

- A DMZ host is not protected by the firewall of the router. A hacker may leverage the DMZ host to attack your LAN. Therefore, enable the DMZ function only when necessary.
- Manually set the IP address of the LAN computer that functions as a DMZ host (Refer to [IP-MAC binding](#) function), as a changeable IP address may result in DMZ function failures.
- Security software, antivirus software, and the built-in OS firewall of the computer may cause DMZ function failures. Disable them when using the DMZ function. If the DMZ function is not required, you are recommended to disable it and enable your firewall, security, and antivirus software.

### Configuration procedure

- Step 1** Choose **Advanced**, and move to the **DMZ Host** module to enter the configuration page.
- Step 2** Set **Host IP Address** to the IP address of a computer that you want to set as the DMZ host.
- Step 3** Click **OK** at the bottom of the page.




----End

## 10.7 UPnP

UPnP is short for Universal Plug and Play. This function enables the router to implement automatic port forwarding by automatically detecting UPnP-based application programs and enabling ports on the router for the applications. It is generally used for P2P programs, such as BitComet and AnyChat, and helps increase the download speed.


Choose **Advanced**, and move to **UPnP** module to enter the configuration page. It is enabled by default. See the following figure.



## 10.8 Firewall

The firewall function helps the router avoid the host on WAN to Ping the WAN IP address to prevent itself from exposing itself, meanwhile protect the router against external Ping attacks.

Choose **Advance**, and move to the **Firewall** module to enter the configuration page. It is enabled by default. See the following figure.



## 11.1 Overview

Internet Protocol version 6 (IPv6) is the most recent version of the Internet Protocol (IP), the communications protocol that provides an identification and location system for computers on networks and routes traffic across the Internet. IPv6 provides a larger addressing space than Internet Protocol version (IPv4).

This router supports 3 connection types for internet access. An IPv6 transition mechanism is a technology that facilitates the transitioning of the internet from the IPv4 infrastructure to the successor addressing and routing system of IPv6. As IPv4 and IPv6 networks are not directly interoperable, transition technologies are designed to permit hosts on either network type to communicate with each other.

The following is a brief introduction of the 3 connection types.

- **DHCPv6**

The Dynamic Host Configuration Protocol version 6 (DHCPv6) is a network protocol for configuring Internet Protocol version 6 (IPv6) hosts with IP addresses, IP prefixes and other configuration data required to operate in an IPv6 network. It is the IPv6 equivalent of the Dynamic Host Configuration Protocol for IPv4.


- **PPPoEv6**

The Point-to-Point Protocol over Ethernet version 6 (PPPoE) is a network protocol for encapsulating PPP frames inside Ethernet frames. It is the IPv6 equivalent of the Point-to-Point Protocol over Ethernet for IPv4.

- **Static IPv6 Address**

The static IPv6 is a prefix delegation. If you have an IPv6 compliant router, it can accept that prefix delegation and subsequently assign or allow you to assign static IPv6 address to the devices attached to your network.


The module enables you to enable IPv6 function and set up the related parameters for internet access. To access the configuration page, click **IPv6**. By default, the IPv6 function is disabled. The following figure appears when it is enabled.



## Parameter description



Parameter	Description
IPv6 WAN Settings	<p>Select the internet parameter obtaining method of WAN port.</p> <ul style="list-style-type: none"> <li>• <b>DHCPv6:</b> The router obtains information from the upstream device, and no information is required on this page.</li> <li>• <b>PPPoEv6:</b> Your ISP provides you with the PPPoE username and password.</li> <li>• <b>Static IPv6 Address:</b> Your ISP provides you with the IP address, subnet mask, default gateway and DNS information.</li> <li>• <b>6in4 Tunnel:</b> It specifies the connections which use a 6in4 address assignment.</li> <li>• <b>6to4 Tunnel:</b> It specifies the connections which use a 6to4 address assignment.</li> <li>• <b>6rd Tunnel:</b> It specifies the connections which use a 6rd address assignment.</li> </ul>
Connection Type	




Parameter	Description	
IPv6 Address Obtaining Method	When you choose <b>Obtain IPv6 Prefix Delegation</b> , the router can obtain an IPv6 prefix from the upstream DHCP server. It can be enabled only when the WAN connection is <b>DHCPv6</b> or <b>PPPoEv6</b> . It is enabled by default. If it is disabled, you need to set IPv6 LAN prefix length manually.	
IPv6 LAN Address	It specifies two types of IPv6 LAN address assignment. <ul style="list-style-type: none"> <li>• <b>Auto</b>: The router auto-generates an IPv6 LAN address.</li> <li>• <b>Manual</b>: You need to set the IPv6 LAN address manually.</li> </ul>	
IPv6 LAN Prefix Length	It specifies two types IPv6 LAN prefix address assignment. <ul style="list-style-type: none"> <li>• <b>Auto</b>: The router auto-generates an LAN Prefix.</li> <li>• <b>Manual</b>: You need to set the IPv6 LAN Prefix manually.</li> </ul>	
DHCPv6	Used to enable/disable the DHCPv6 server. If it is disabled, you have to manually set IP address settings for your connected devices for internet access.	
IPv6 LAN Settings	It specifies the assignment type of DHCPv6 address for the clients connected to the router.	
DHCPv6 Address Assignment Method	<ul style="list-style-type: none"> <li>• <b>Auto</b>: The router auto-assigns IP addresses to the clients automatically.</li> <li>• <b>Manual</b>: You need to set the IP address pool of the router manually.</li> </ul>  <b>NOTE</b> Start/End ID are the start IPv6 address and end IPv6 address of the DHCP server's IPv6 assignment.	
IPv6 DNS	It specifies the assignment type of DNS address for the clients connected to the router. <ul style="list-style-type: none"> <li>• <b>Auto</b>: The router assigns the DNS address of WAN to the clients automatically.</li> <li>• <b>Manual</b>: You need to set the IPv6 DNS address manually.</li> </ul>	
Connection Type	It specifies the IPv6 connection type of the WAN port.	
IPv6 WAN Address	It specifies the IPv6 address of the WAN port.	
Default IPv6 Gateway	It specifies the IPv6 gateway address of the WAN port.	
IPv6 Status	IPv6 LAN Address	It specifies the IPv6 address of the LAN port.
Primary IPv6 DNS	It specifies the IPv6 address of the primary DNS server assigned by the DHCP server to LAN devices.	
Secondary IPv6 DNS	It specifies the IPv6 address of the secondary DNS server assigned by the DHCP server to LAN devices.	

## 11.2 Setting up an internet connection with DHCPv6

### Configuration procedures:

- Step 1** Click **IPv6** to enter the configuration page.
- Step 2** Switch the IPv6 button from  to  state.
- Step 3** Select **DHCPv6** from the **Connection Type** drop-down list box.
- Step 4** Select the **IPv6 LAN Address** type.
- Step 5** Enable/disable **DHCPv6** of the router.
- Step 6** Select the **DHCPv6 Address Assignment Method** as required, and set the related parameters.
- Step 7** Select the **IPv6 DNS** mode as required, and set the related parameters.
- Step 8** Click **OK** at the bottom of the page.



IPv6

IPv6

IPv6 WAN Settings

Connection Type

IPv6 Address Obtaining Method  Obtain IPv6 Prefix Delegation

IPv6 LAN Settings

IPv6 LAN Address

IPv6 LAN Prefix Length

DHCPv6

DHCPv6 Address Assignment Method



IPv6 DNS


---End

After the settings take effect, check the **IPv6 Status**. If there are IP addresses of IPv6 WAN address, default IPv6 gateway and related parameters, the router is connected to the internet successfully.

## 11.3 Setting up an internet connection with PPPoEv6

Configuration procedures:

- Step 1** Click **IPv6** to enter the configuration page.
- Step 2** Switch the **IPv6** button from  to  state.
- Step 3** Select **PPPoEv6** from the **Connection Type** drop-down list box.
- Step 4** Enter the **PPPoE username** provided by your ISP.
- Step 5** Enter the **PPPoE password** provided by your ISP.
- Step 6** Select the **IPv6 LAN Address** type.
- Step 7** Enable/disable **DHCPv6** of the router.
- Step 8** Select the **DHCPv6 Address Assignment Method** as required, and set the related parameters.
- Step 9** Select the **IPv6 DNS** mode as required, and set the related parameters.
- Step 10** Click **OK** at the bottom of the page.





The screenshot displays the IPv6 configuration interface. At the top, the 'IPv6' status is shown as a green toggle switch. Below this, the 'IPv6 WAN Settings' section includes a 'Connection Type' dropdown menu set to 'PPPoEv6', two empty text input fields for 'PPPoE Username' and 'PPPoE Password', and a checked checkbox for 'Obtain IPv6 Prefix Delegation Method'. The 'IPv6 LAN Settings' section features five dropdown menus: 'IPv6 LAN Address' (Auto), 'IPv6 LAN Prefix Length' (Auto), 'DHCPv6' (Enable), 'DHCPv6 Address Assignment Method' (Auto), and 'IPv6 DNS' (Auto).


---End

After the settings take effect, check the **IPv6 Status**. If there are IP addresses of IPv6 WAN address, default IPv6 gateway and related parameters, the router is connected to the internet successfully.

## 11.4 Setting up an internet connection with static IPv6 address

Configuration procedures:

- Step 1** Click **IPv6** to enter the configuration page.
- Step 2** Switch the **IPv6** button from  to  state
- Step 3** Select **Static IPv6 Address** from the **Connection Type** drop-down list box.
- Step 4** Enter the **IPv6 Address** provided by your ISP.
- Step 5** Enter the **Default IPv6 Gateway** for your IPv6 internet connection.
- Step 6** Enter the **Primary/Secondary IPv6 DNS** provided by your ISP. If your ISP provides only one DNS address, keep the secondary IPv6 DNS blank.
- Step 7** Select the **IPv6 LAN Address** type and set the related parameter.
- Step 8** Enter the **IPv6 LAN Prefix Length**.
- Step 9** Enable/disable **DHCPv6** of the router.
- Step 10** Select the **DHCPv6 Address Assignment Method** as required, and set the related parameters.
- Step 11** Select the **IPv6 DNS** type and set the related parameters.
- Step 12** Click **OK** at the bottom of the page.



The screenshot displays the IPv6 configuration interface, divided into two main sections: IPv6 WAN Settings and IPv6 LAN Settings.

**IPv6 WAN Settings:**

- IPv6:** A toggle switch is turned on (green).
- Connection Type:** A dropdown menu is set to "Static IPv6 Address".
- IPv6 Address:** Two empty input fields separated by a slash (/).
- Default IPv6 Gateway:** One empty input field.
- Primary IPv6 DNS:** One empty input field.
- Secondary IPv6 DNS:** One empty input field.

**IPv6 LAN Settings:**

- IPv6 LAN Address:** A dropdown menu is set to "Auto".
- IPv6 LAN Prefix Length:** A dropdown menu is set to "Manual", followed by an empty input field and "/ 64".
- DHCPv6:** A dropdown menu is set to "Enable".
- DHCPv6 Address Assignment Method:** A dropdown menu is set to "Auto".
- IPv6 DNS:** A dropdown menu is set to "Auto".

---End

After the settings take effect, check the **IPv6 Status**. If there are IP addresses of IPv6 WAN address, default IPv6 gateway and related parameters, the router is connected to the internet successfully.

# 12

# Administration


This section describes how to manage and maintain your router and home network.

## 12.1 Login password

To ensure network security, a complex login password is recommended. A login password consisting of more types of characters, such as uppercase letters and lowercase letters, has higher security.

**Configuration procedure:**

- Step 1** Choose **Administration**, and move to the **Login Password** module to enter the page.
- Step 2** Set a new password (5-32 characters) in **New Password** box.
- Step 3** Repeat the new password in **Confirm Password** box.
- Step 4** Click **OK** at the bottom of the page.



The screenshot shows a web interface for setting a login password. At the top, the title is "Login Password". Below the title, there are two rows of input fields. The first row is labeled "New Password" and has a dropdown menu with the option "Digits and letters only" selected. The second row is labeled "Confirm Password" and has a dropdown menu with the option "Confirm Password" selected.


---End

The page will redirect to the login page. And you need to use the new password to login again.

## 12.2 WAN parameters

In the **WAN Parameters** module, you can check and modify MTU value, clone MAC address and modify WAN speed.

Choose **Administration** and move to the **WAN Parameters** module to enter the configuration page.



WAN Parameters

MTU	1500	Do not change if unnecessary.
Clone MAC Address	Restore Default MAC	Default MAC Address: C8:3A:35:17:F0:40
WAN Speed	1000 Mbps auto-negotiation	Current speed: 100 Mbps full duplex

### MTU

MTU specifies the maximum size of packet that the router can transmit. MTU varies based on connection types. The default setting is recommended.

You can try to change the MTU when:

- You cannot access some specific websites or encrypted websites (such as E-banking or Paypal websites).
- You cannot access a FTP or POP server.

You can try reducing the value of MTU gradually from 1500 until the problem is resolved. (The recommended range is 1400 to 1500.)

MTU	Application
1500	It is commonly used for ADSL and non-VPN dial-up connections.
1492, 1480	It is used for ADSL dial-up connections.
1472	It is the maximum value for the ping command. (A packet with a larger size is fragmented.)
1468	It is used for DHCP connections.
1436	It is used for VPN or PPTP connections.

### Clone MAC Address

If your ISP binds your account with MAC Address of your computer that used to verify internet connectivity after you subscribed to the internet service, only this computer can access the internet with the account. In this case, you can use the Clone MAC Address function to clone the MAC address of this computer to the WAN port of the router to achieve network sharing.

Restore Default MAC is the default method to clone MAC address of the router. If there is no need to clone MAC address, retain the default settings.


Here are two scenarios to clone MAC address.

**Scenario 1:** The computer used to manage the router is the computer that used to access the

internet.

### Configuration procedure:

- Step 1** Choose **Administration**, and move to the **WAN Parameters** module to enter the configuration page.
- Step 2** Set **Clone MAC Address** to **Clone Local Host MAC**.
- Step 3** Click **OK** at the bottom of the page.



The screenshot shows the 'WAN Parameters' configuration page. It contains three rows of settings:


- MTU:** A dropdown menu is set to '1500'. To its right, the text reads 'Do not change if unnecessary.'
- Clone MAC Address:** A dropdown menu is set to 'Clone Local Host MAC'. To its right, the text reads 'Local Host MAC Address: 74:27:EA:69:80:04'.
- WAN Speed:** A dropdown menu is set to '1000 Mbps auto-negotiation'. To its right, the text reads 'Current speed:100 Mbps full duplex'.

---End

**Scenario 2:** The computer used to manage the router is not the computer that used to access the internet. And you need to get the MAC address of the computer that can access the internet.

### Configuration procedure:

- Step 1** Choose **Administration**, and move to **WAN Parameters** module to enter the configuration page.
- Step 2** Set **Clone MAC Address** to **Manual**.
- Step 3** Enter the MAC address of the computer that can access the internet in the format of `XX:XX:XX:XX:XX:XX`.



The screenshot shows the 'WAN Parameters' configuration page. It contains three rows of settings:

- MTU:** A dropdown menu is set to '1500'. To its right, the text reads 'Do not change if unnecessary.'
- Clone MAC Address:** A dropdown menu is set to 'Manual'. To its right, there is a text input field containing the MAC address 'C8:3A:35:17:F0:40'.
- WAN Speed:** A dropdown menu is set to '1000 Mbps auto-negotiation'. To its right, the text reads 'Current speed:100 Mbps full duplex'.

- Step 4** Click **OK** at the bottom of the page.

---End

## WAN Speed

WAN speed specifies the speed of the WAN port. By default, the throughput of the WAN port is Auto-negotiation. Change the setting only when necessary. If the router cannot access the internet after you set up it correctly with a 10 Mbps upstream device, you can change WAN speed to 10 Mbps auto-negotiation to achieve negotiation.



## 12.3 LAN parameters

In this section, you can view and modify the LAN IP address and DHCP server parameters of the router.

The DHCP server can automatically assign IP addresses, subnet masks, gateways and other related parameters to the clients of the router.

Choose **Administrator**, and move to the **LAN Parameters** module to enter the configuration page.

LAN Parameters


LAN IP Address	<input type="text" value="192.168.0.1"/>
Subnet Mask	<input type="text" value="255.255.255.0"/>
DHCP Server	<input checked="" type="checkbox"/> Enable <small>If this function is disabled, the router stops assigning IP addresses to clients.</small>
Start IP Address	192.168.0. <input type="text" value="100"/>
End IP Address	192.168.0. <input type="text" value="200"/>
Preferred DNS Server	<input type="text" value="192.168.0.1"/>
Alternate DNS Server	<input type="text"/>

### Parameter description

Parameter	Description
LAN IP Address	It specifies the LAN IP address of the router, which is also the management IP address, for logging in to the router web UI.
Subnet Mask	It specifies the subnet mask of the LAN port.
DHCP Server	It specifies whether to enable DHCP server.
Start IP Address/End IP Address	It specifies the range of IP addresses that can be assigned to devices connected to the router.
Preferred DNS Server	It specifies the preferred DNS address of the router, which is used to assign to the clients. It is the LAN IP address of the router by default. You can change it if necessary.
Alternate DNS Server	It specifies the alternate DNS address of the router used to assign to the clients. It is an optional field and is left blank by default.

## 12.4 Remote web-based management

Generally, the web UI of the router can only be accessed on devices that are connected to the router by a LAN port or wireless connection. When you encounter a network fault, you can ask for remote technical assistance, which improves efficiency and reducing costs and efforts. By default, this function is disabled. The following figure displays as below when this function is enabled.



Remote Web-based Management

Remote Web-based Management  Enable If this function is enabled, you can manage the router through the internet.


Management IP Address

Port

### Configuring remote web-based management

Configuration procedure:

- Step 1** Choose **Administration**, and move to the **Remote Web-based Management** module to enter the configuration page.
- Step 2** Select the **Enable** option.
- Step 3** Set **Management IP Address** to **Specific**, and enter a specified IP address.
- Step 4** Enter a port number used to access the router remotely.
- Step 5** Click **OK** at the bottom of the page.



Remote Web-based Management

Remote Web-based Management  Enable If this function is enabled, you can manage the router through the internet.


Management IP Address

Port

---End

### Parameter description


Parameter	Description
Remote Web-based Management	Used to enable/disable Remote Web-based Management function. It is disabled by default.
Management IP Address	<p>It specifies the IP address to manage the router remotely.</p> <ul style="list-style-type: none"><li><b>All:</b> It indicates that all internet users can access the web UI of the router. It is not recommended to select this option for network security.</li><li><b>Specific:</b> It indicates that only the user with the specified public IP address is allowed to access the web UI of the router remotely. If the host for remote access is in an intranet, enter the public IP address of the computer's gateway here.</li></ul>

Parameter	Description
	It specifies the port number to access the router remotely. It is <b>80</b> by default, and can be modified if necessary.
	 <b>TIP</b>
Port	Port 1 to 1024 are occupied by well-known services. It is recommended to modify the port to be in the range from 1025 to 65535.  To access the web UI of the router by the URL: <a href="http://WAN IP address:port number">http://WAN IP address:port number</a> . If DDNS is enabled on the router, you can access the web UI by <a href="http://WAN domain name:port number">http://WAN domain name:port number</a> .

## An example of configuring remote web-based management

An AC8 is used to set up a network to in an apartment, and needs to be logged in and managed over the internet. Assume the public IP address of the router is 102.105.106.55 and that of the computer for remote management is 210.76.200.101.

The following figure shows the application scenario.



Computer 1 (web server)



The computer used to remotely log in to the web UI of the router must be assigned a public IP address. If it is assigned a private IP address, use the public IP address of the router to which the computer connects for remote login. Private IP addresses are not applicable to remote management.

### Configuration procedure:

- Step 1** Choose **Administration**, and move to the **Remote Web-based Management** module to enter the configuration page.
- Step 2** Check the **Enable** option.
- Step 3** Set **Management IP Address** to **Specific**, and enter **210.76.200.101**.
- Step 4** Click **OK** at the bottom of the page.

Remote Web-based Management

Remote Web-based Management  Enable If this function is enabled, you can manage the router through the internet.

Management IP Address

Port

---End

After the configuration is saved, use <http://102.105.106.55:8888> to access the web UI of the router on computer 2.

## 12.5 Date & Time

If the system time of the router is incorrect, time-based functions of the router cannot take effect correctly, including the WiFi schedule, parental controls and Automatic Maintenance functions. When the configuration with the Quick Setup Wizard is complete, the router synchronizes its system time with the computer used to configure the router. You can change the setting manually.

Choose **Administration**, and move to the **Date & Time** module to enter the configuration page.

Date & Time

Time Zone	<input type="text" value="(GMT+08:00)Beijing, Chongqing, Hong Kong, Urumqi"/>	
Current Time	2019-08-15 10:07:54	The current date and time have been synchronized with those of the internet.


## 12.6 Device management

This module describes how to reboot, reset, and upgrade the router, how to back up your current configuration and restore the router to previous configuration, and how to view the system logs and functions enabled or disabled.

### Reboot router

If a setting fails to take effect or the router fails to work properly, you can try rebooting the router.

Choose **Administration**, and move to the **Device Management** module to enter the configuration page. Click **Reboot**, confirm, and the router will restart. When the progress bar completes, it indicates the router completes restart.



Rebooting the router will disconnect all the connections. Please reboot the router when the network is idle.

### Restore factory settings

If you are uncertain about why the internet is inaccessible through the router or you forget the login password of the router, you can reset the router.

The router can be reset on the web UI or using the **WPS/RST** button.




- Resetting the router is not recommended unless you forget your login password or under the requirement of Tenda technical support. You can access the internet only after reconfiguring the router.
- Ensure that the power supply of the router is normal when the router is reset.
- The default login IP address is 192.168.0.1, and login password is admin after resetting.

### Resetting the Router on the Web UI


**Step 1** Choose **Administration**, and move to the **Device Management** module to enter the

configuration page.

**Step 2** Click **Reset**.



**Step 3** Click **OK** in the popup window.



---End

Wait for the progress bar to complete.

### Resetting the Router Using the Reset Button


Hold down the **WPS/RST** button of the router for about 8 seconds and release it when the LED indicator blinks fast. The router is reset successfully when the LED indicator lights up.

### Backup/Restore configuration

In this module, it allows you to back up the current configuration of the router to your computer. You are recommended to back up the configuration after the settings of the router are significantly changed, or the router works in a good condition.

After you restore the router to factory settings or upgrade it, you can use this function to restore a configuration that has been backed up.


To back up or restore the configuration of your router, choose **Administration**, move to the **Device Management** module and perform the backup or restoring procedures.



## Export system log

This function logs all key events that occur after the router is started. If you encounter a network fault, you can turn to system logs for fault rectification.

Choose **Administration**, and move to the **Device Management** module to access the configuration page.



Click **Export** to save system logs to your local computer.

## Upgrade firmware

This function enables the router to obtain the latest functions and more stable performance. The router supports local firmware upgrade and online firmware upgrade.



## Local upgrade




- To enable a successful upgrade, ensure that the firmware is applicable to the router.
- When you are upgrading a firmware, do not power off the router.

**Step 1** Go to [www.tendacn.com](http://www.tendacn.com), download a firmware version of the router to your computer and unzip it.


**Step 2** Choose **Administration**, and move to the **Device Management** module to access the configuration page.

**Step 3** Click **Local Upgrade**.



**Step 4** Select the corresponding firmware version, and click **Open**.

**Step 5** Click **OK** in the appearing dialog box.



---End

Wait until the progress bar is complete. Log in to the web UI of the router again. Choose **Status > System Information** and check whether the upgrade is successful based on **Firmware Version**.



For better performance of the new firmware, you are recommended to reset the router to factory default settings and re-configure the router when the upgrading completes.

## Online upgrade

When the router is connected to the internet, it auto-detects whether there is a new firmware and displays the detected information on the page. You can choose whether to upgrade to the latest

firmware. If you want to upgrade the firmware, click **Upgrade** and the router upgrades the firmware automatically.

**Configuration procedure:**

**Step 1** Choose **Administration > Device Management** on the router web UI.

**Step 2** Click **Online Upgrade**.

---End

Wait until the progress bar is complete. Log in to the web UI of the router again. Choose **Status > System Information** and check whether the upgrade is successful based on **Firmware Version**.



For better performance of the new firmware of the router, you are recommended to reset the router to factory default settings and re-configure the router when the upgrading completes.

## Automatic Maintenance

Automatic maintenance enables you to make the router restart regularly. It helps improve the stability and service life of the router.

To configure the automatic maintenance function, choose **Administration**, and move to the **Device Management**. If this function is enabled, the router reboots during 03:00~05:00 a.m. every day when the traffic is lighter than 3 KB/s. By default, this function is enabled.


The screenshot shows the 'Device Management' section of a router's web interface. It contains several rows of management actions, each with a corresponding button: 'Reboot Router' with a 'Reboot' button; 'Restore Factory Settings' with a 'Reset' button; 'Backup/Restore Configuration' with 'Backup' and 'Restore' buttons; 'Export System Log' with an 'Export' button; and 'Upgrade Firmware' with 'Local Upgrade' and 'Online Upgrade' buttons. Below these buttons, the text 'Current Firmware Version: V02.03.01.50\_multi' is displayed. At the bottom, the 'Automatic Maintenance' option is highlighted with a red dashed box. It is currently checked and labeled 'Enable', with a descriptive note: 'If this function is enabled, the router reboots during 02:00 a.m. to 05:30 a.m. every day when the traffic is less than 3 KB/s.'


# Appendix

## A.1 Configuring the computer to obtain an IP address automatically


Perform the configuration procedures corresponding to [Windows 8](#), [Windows 7](#), and [Windows 10](#) as required. A computer installed with a wired network adapter is used as an example to describe the procedures. The procedures for configuring computers installed with a wireless network adapter are similar.

### A.1.1 Windows 8


**Step 1** Right-click  in the lower-right corner of the desktop and choose **Open Network and Sharing Center**.




**Step 2** Click **Ethernet** and then **Properties**.



**Step 3** Double-click **Internet Protocol Version 4 (TCP/IPv4)**.




**Step 4** Select **Obtain an IP address automatically** and **Obtain DNS server address automatically**, and click **OK**.




**Step 5** Click **OK** in the **Ethernet Properties** window.


**----End**

## A.1.2 Windows 7


**Step 1** Click  in the lower-right corner of the desktop and choose **Open Network and Sharing Center**.




**Step 2** Click **Local Area Connection** and then **Properties**.



**Step 3** Double-click **Internet Protocol Version 4 (TCP/IPv4)**.




**Step 4** Select **Obtain an IP address automatically** and **Obtain DNS server address automatically**, and click **OK**.



**Step 5** Click **OK** in the **Local Area Connection Properties** window.


**----End**

## A.1.3 Windows 10


**Step 1** Click  in the lower-right corner of the desktop and choose **Network settings**.




**Step 2** Click **Change adapter options**.




**Step 3** Right click on the connection which is being connected, and then click **Properties**.



**Step 4** Double-click **Internet Protocol Version 4 (TCP/IPv4)**.



**Step 5** Select **Obtain an IP address automatically** and **Obtain DNS server address automatically**, and click **OK**.



**Step 6** Click **Close** in the **Ethernet Properties** window.

**----End**



## A.2 Default parameters

Parameter		AC8	AC7	AC5
LAN Parameters	IP Address	192.168.0.1		
	Subnet Mask	255.255.255.0		
DHCP Server	DHCP Server	Enabled		
	Start IP Address	192.168.0.100		
	End IP Address	192.168.0.200		
	Preferred DNS Server	192.168.0.1		
Operating Mode		Router mode		
Wireless Settings	WiFi Name	Tenda_XXXXXX. XXXXXX indicates the last 6 characters of the MAC address of the router.		
	WiFi Password	None		
IPv6		Disabled		